



VIZM.EX4390 Fittings, Rubber Gasketed

[Page Bottom](#)

Fittings, Rubber Gasketed

[See General Information for Fittings, Rubber Gasketed](#)

QINGDAO HILYWILL ADVANCED MATERIALS TECHNOLOGY CO LTD

EX4390

SHANGTUAN COMMUNITY

HETAO ST

CHENGYANG DISTRICT

QINGDAO, SHANDONG 266113 CHINA

Ductile-iron pipe couplings and flange adapters consisting of housings, rubber gaskets and steel bolts and nuts:

| Model | Groove Type | Pipe Schedule | Size In. | Rated Pressure (psig) |
|-----------|-------------|---------------|------------------------------------|-----------------------|
| Style 10 | Rolled | 5, EF | 1-1/4, 1-1/2, 2 | 300 |
| Style 10 | Rolled | 10 | 1-1/4, 1-1/2, 2, | 500 |
| | | | 2-1/2, 3 | |
| Style 10 | Rolled | 10 | 4, 6, 8 | 300 |
| Style 10 | Cut, Rolled | 40 | 1-1/4, 1-1/2, 2 | 500 |
| | | | 2-1/2, 3 | |
| Style 10 | Cut, Rolled | 40 | 4, 6, 8, 10, 12 | 300 |
| Style 10 | Rolled | DT | 1-1/4, 1-1/2, 2 | 300 |
| Style 10 | Rolled | DL | 1-1/4, 1-1/2, 2 | 300 |
| Style 10 | Rolled | BLT | 1-1/4, 1-1/2, 2 | 300 |
| Style 10 | Rolled | DF | 1-1/4, 1-1/2, 2, | 300 |
| | | | 2-1/2, 3, 4 | |
| Style 10 | Rolled | SF | 1-1/4, 1-1/2, 2, | 300 |
| | | | 2-1/2, 3 | |
| Style 10 | Rolled | SF | 4 | 175 |
| Style 10 | Rolled | EZ | 4 | 300 |
| Style 10L | Rolled | 10, 40 | 1-1/4, 1-1/2, 2, 2-1/2, 3, 4, 6, 8 | 175 |
| Style 5 | Cut, Rolled | 10/40 | 2, 2-1/2, 3, 4 | 300 |
| Style 5 | Cut, Rolled | 10/40 | 6, 8 | 300 |
| Style 5 | Cut, Rolled | 40 | 10, 12 | 300 |
| Style 5 | Rolled | SF | 2, 2-1/2, 3 | 300 |
| Style 5 | Rolled | 10, 40 | 1-1/4, 1-1/2 | 175 |
| 5A | Roll | 10 | 1-1/4, 1-1/2, 2, 2-1/2, 3, 4 | 300 |
| 5A | Roll, Cut | 40 | 1-1/4, 1-1/2, 2, 2-1/2, 3, 4 | 300 |
| 5A | Roll | 10 | 6, 8 | 175 |
| 5A | Roll, Cut | 40 | 6, 8 | 175 |

| | | | | |
|----------|-------------|----------|------------------------------------|-----|
| 5A | Roll | BS 1387M | 165 mm | 300 |
| 5A | Roll | BS 1387L | 76mm | 300 |
| Style 5L | Rolled | 10, 40 | 1-1/4, 1-1/2, 2, 2-1/2, 3, 4, 6, 8 | 175 |
| Style 25 | Rolled | 10 | 2x1-1/2, 2-1/2x1-1/2, | 300 |
| | | | 2-1/2x2, 3x2, 3x2-1/2, | |
| | | | 4x2-1/2, 4x2, 4x3 | |
| Style 25 | Cut, Rolled | 40 | 2x1-1/2, 2-1/2x1-1/2 | 300 |
| | | | 2-1/2x2, 3x2, 3x2-1/2, | |
| | | | 4x2-1/2, 4x2, 4x3 | |
| Style 25 | Rolled | 10 | 6x4 | 250 |
| Style 25 | Cut, Rolled | 40 | 6x4 | 250 |
| Style 14 | Rolled | 10/40 | 2, 2-1/2, 3, 4, | 250 |
| | | | 6, 8 | |
| Style 11 | Rolled | 10 | 3, 4, 6, 8 | 300 |
| Style 11 | Rolled/Cut | 40 | 3, 4, 6, 8 | 300 |

10 refers to Schedule 10 steel pipe

40 refers to Schedule 40 steel pipe

DT, DL, BLT and DF refer to Dyna-Thread, Dyna-Light, Black Lightwall Threadable and Dyna-Flow Listed Steel Sprinkler Pipes manufacturerd by Allied Tube & Conduit Corp.

EF refers to Listed steel sprinkler pipe manufacturer by Ball Moose Tube Co.

EZ refers to Listed EZ-Flow steel sprinkler pipe manufacturer by Northwest Pipe Co., Inc.

SF refers to Listed Super-Flo steel sprinkler pipe manufacturer pipe manufactured by Allied Tube & Conduit Corp.

BS1387L refers to BS1387 in accordance with British Standard 1387 Light wall thickness.

BS1387M refers to BS1387 in accordance with British Standard 1387 Medium wall thickness.

Side Outlet

| Model | Outlet Type | Pipe | Size (in.) | Rated Pressure (psig) |
|-----------|-------------|------|--|-----------------------|
| Style 16 | Threaded | 10 | 4x1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3 | 300 |
| Style 16 | Threaded | 10 | 3x1/2, 3/4, 1, 1-1/4, 1-1/2, 2 | 300 |
| Style 16 | Threaded | 10 | 2, 2-1/2x1/2, 3/4, 1, 1-1/4, 1-1/2 | 300 |
| Style 16 | Threaded | 10 | 6x1-1/4, 1-1/2, 2, 2-1/2, 3, 4 | 300 |
| Style 15G | Grooved | 10 | 3x1-1/2, 2 | 300 |
| Style 15G | Grooved | 10 | 4x1-1/2, 2, 2-1/2, 3 | 300 |
| Style 15G | Grooved | 10 | 6x1-1/2, 2, 2-1/2, 3, 4 | 300 |

Model 16 in the 1/2, 3/4, and 1 in. nominal outlet sizes is intended for direct connection to sprinklers.

Model 15G and 16 in the 1 in. and larger nominal outlet sizes are intended for connection to system piping.

The pipe is to be grooved in accordance with the manufacturer's installation instructions. Style 10 rubber gasket fittings are suitable for use in dry pipe systems for temperatures to -40 F (-40 C).

These couplings may be expected to form joints, which do not need restraint.

Trademark and/or Tradename: "CPS"

Last Updated on 2012-03-26

When the UL Leaf Mark is on the product, or when the word "Environment" is included in the UL Mark, please search the [UL Environment database](#) for additional information regarding this product's certification.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2014 UL LLC".